



WHITE ISO CONTACTLESS SMART CARD

Specifications

Contactless cards or RFID Cards are the perfect solution when you require more security and control in your company or for your event. Contactless cards perfect for, Access control systems in hotel rooms, Public transportation systems, Payment (schools, companies, museums, stadiums, etc.), Access control at events, Identification (government ID, Hospital badge, insurance card, etc.), Access cards for marinas or camping sites, VIP access cards (golf club, dance club etc.), Distinguishing between different access levels (e.g. VIP's)

Electrical Characteristics

Operating Frequency Range	125 KHz (LF) 13.56 MHz (HF) 860-960 MHz (UHF)
International Standard	ISO 14443,ISO 15693,ISO18000-6C
Chip Type*	LF – EM4100,T5577 HF – MF Ultralight, MF1k,MF4k,MF Desfire, MF Desfire EV1, ICODE SLI UHF – NXP G2XM, Alien Higgs3,Impinj Moza5

Mechanical Characteristics

Size	85.6x54x 0.8 mm
Material	PVC,PET
Color	white or as customized
Reading test	100% read tested

General Characteristics

Operating Temperature	-20°C to +50°C
-----------------------	----------------

Additional Services/Options

Pre encoding	On request**
Customization	Logo/text printing on request**

*other ICs available on request

** Available as option at extra cost

Contact Cmrfid Technologies for additional information..

Shanghai Cmrfid Technology Co.,Ltd

Room206 ,buliding1,NO.3279Sanlu Rd.Minhang District,Shanghai201112,China

Tel: +86 18601658083 Fax: +86 021 60717851

Cmrfid reserves the right to change/update any information provided above without prior notice.